

UNI-H2

Face Recognition Terminal

OVERVIEW

The Uni-H2 face recognition terminal adopts a deep learning algorithm, which helps to recognise the face faster with higher accuracy. It also supports multiple authentication modes: face and RFID card authentication. It can be applied in multiple indoor scenarios such as buildings, enterprises, financial industries, and other important areas. The terminal supports a Wi-Fi connection.



Facial Recognition



RFID Card



Wi-Fi Enabled



HARDWARE		CAPACITY	
Display	4.3 inch	Card	3,000
Resolution	480 x 272	Face Template	1,500
Type	LCD	Log	100,000
Operation Method	Capacitive Touch Screen	Voltage	12V D.C 1A
Dimensions	118.4 x 118.4 x 21.8 mm	Card Reading Frequency	13.56 MHz
Verification Time	< 2 second	Face Recognition Distance	0.3 to 1.5m
Wired Network	10M / 100M self-adaptive	OPERATING CONDITIONS	
Wi-Fi	Supported	Temperature	10°C to 40°C
Pixel	2MP	Humidity	0 to 90% (non-condensing)
Lens	x2	Power Supply	12VDC / 1A
Video Standard	PAL (default) and NTSC		

We've offered proudly South African developed solutions since 1945 for the local and international market. Our easy to use solutions are configured to your requirements to ensure total accuracy. Uniclox is your One-Stop Shop in Turnkey Solutions, ensuring peace of mind.



300 Hennie Alberts Street
Alrode South, Alberton, 1451



011 439 2000



sales@uniclox.com
www.uniclox.co.za